HUBER+SUHNER® DATA SHEET Coaxial Panel Connector: 22_BK-50-0-2/133_U



Description

Straight bulkhead receptacle jack

Interface standards



Impedance 50 Ω Interface frequency max. GHz

Mechanical Data

Weight 0.0016 kg

Environmental Data

Operating Temperature °C to °C 2002/95/EC (RoHS) compliant

Material Data

Piece Parts Material

Copper Beryllium Alloy Centre contact

Outer contact **Brass** Body Brass Insulator PFA / PTFE Fastening nut Brass

Related Documents

Outline drawing DOU-00011236 Mounting hole DOU-00008855

Ordering Information

22_BK-50-0-2/133_UE Single package

Surface Plating

Gold Plating (without Nickel underplating)

SUCOPLATE (R) Plating SUCOPLATE (R) Plating

SUCOPLATE (R) Plating

HUBER+SUHNER is certified according to ISO 9001 and ISO 14001

WAIVER!
It is exclusively in written agreements that we provide our customers with warrants and representations as to the technical contained specifications and/or the fitness for any particular purpose. The facts and figures herein are carefully compiled to the best of our knowledge, but they are intended for general informational purposes only.

HUBER+SUHNER - Excellence in Connectivity Solutions

Document: DOC-0000189010 I Issued: 17.01.13 Uncontrolled Copy Page 1/1



RF Technology **9100 Herisau, Switzerland** Phone +41 (0)71 353 41 11 +41 (0)71 353 45 90 Fax www.hubersuhner.com